skyVac INTERCEPTOR

Mobile Wet & Dry Industrial Gutter Vacuum

Machine Specification | EXTERNAL USE

Motor Wattage:	3600 Watt Max (5.5HP Honda Petrol Engine)
Water Lift:	155"
Air Flow Movement:	8,000 LPM
Cyclonic Entry Port:	50mm
Container:	90 Litre
Weight:	78kg Pull Start / 87kg Key Start
Decibel Level:	107 dB
Dimensions (cm):	140(l) x 63(w) x 104.5(h)

FULLY MOBILE

ONBOARD HONDA ENGINE

skyVac ELITE Clamped Pole

POLE TYPE:	**CLAMPED**
Material:	Carbon Fibre
Weight per 1.5m:	280g
Diameter:	50mm
Length:	1.5m
Reach:	12m/40ft

Elite Suction Pole

Vac Release Cuff

Patent Pending
No: GB1713830.6

Hairpin Neck Tool Holder

EU Registered Design
No: 008458913

Package include

· 1.5M skyVac® Elite Suction Poles (50mm) · 1 x Vac Release Cuff · 1 x Anti-Block Hairpin Neck tool holder
· 7.5M Wire Reinforced 50mm Suction Hose · 6 x Gutter End tools. 2 x Cuffs · skyVac® Pole & tools Carry Case

Available with 4, 6, or 8 poles

Key Features

Onboard Honda Motor

Blow Function Feature

Optional Sieve Basket

Optional Key Start

Carbon Fibre Poles

SC000472-09/21

spinaclean ltd
home of skyVac

Email: **info@spinaclean.com** Call: **01604 968700**